

County Surveyor's Record, Douglas County, Oregon

3261

Subdivisions, T. 29 S., R. 7 W.

*

CHAINS

A white oak, 10 ins, diam., bears S.62 $\frac{1}{2}$ *W., 11 lks. dist., marked T. 29 S R 7 W S 32 B T.

A white oak, 12 ins. diam., bears N.84 $\frac{1}{2}$ *W., 63 lks. dist., marked T 29 S R 7 W S 29 B T.

Land, rolling and mountainous.

Soil, clay loam, 2nd rate.

Timber, fir, oak, pine, laurel, and cedar.

Undergrowth, hazel, laurel, fir, and willow.

S.0*19*W., bet. secs. 32 and 33.

Over rolling land, through scattering timber and dense undergrowth.

Ascend over gradual NW. slope, 202 ft.

4.50 Dry wash, 65 lks. wide, 20 ft. deep, course W.

17.00 Enter heavy timber, bears E. and W.

23.20 Ditch, 15 lks. wide, 4 ft. deep, course NE.

26.85 Draw, course NW.

37.70 Draw, course NW.; ascend N.slope, 38 ft.

39.75 Intersect the point for $\frac{1}{4}$ sec. cor., as restored by county surveyor at cor. of fence, bears S. and W. Ford's notes do not describe any bearing trees at this cor., but a laurel, 36 ins. diam., bears N.14*E., 28 lks. dist., marks are plain and indicate they were made by Ford, and an oak, rotted down, bears S.70*W., 20 lks. dist., marks show on the log.

At the fence cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

S32:S33
1924

from which

A fir; 6 ins. diam., bears E.32*E., 15 lks. dist., marked $\frac{1}{4}$ S 33 B T.

A fir, 7 ins. diam., bears N.27*W., 23 lks. dist., marked $\frac{1}{4}$ S 32 B T.

Thence from the $\frac{1}{4}$ sec. cor.