

CHAINS

S.6*33'W., bet. secs. 32 and 33.

Ascend over NW. slope, 535 ft.

14.25 Old pole fence, bears NE. and SW.

27.30 Intersect the S. bdy. of the TP., at the cor. of secs. 32 and 33, hereafter described.

Land, rolling and mountainous.

Soil, clay loam, 2nd rate.

Timber, fir, laurel, and oak.

Undergrowth, hazel, laurel, and fir.

From the cor. of secs. 28, 29, 32 and 33.

S.89*16'E., bet. secs. 28 and 33.

Over rolling land, through heavy timber and dense undergrowth.

Ascend W. slope, 30 ft.

8.50 Top of spur, slopes NW.; descend gradually 16 ft.

9.85 Draw, spring branch, course NW.; ascend gradual W. slope 195 ft.

19.10 Pole fence, bears N.85*E. and S.85*W.

26.00 Fence, bears N. and S.; enter corn field.

35.55 Leave field, bears N. and S.; fence bears South; enter heavy timber.

39.91 Intersect the point for 1/4 sec. cor., located by measurement from the original bearing trees, both of which are down, but blazes show on SW. tree. ✓

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S28}{S33}$
1924

from which (the original bearing trees)

An oak stump hole, bears S.84*W., 36 lks. dist.,

A pine stump hole, bears N.61*E., 14 lks. dist.,

New bearing trees:

A fir, 12 ins. diam., bears S.50*E., 11 lks. dist., marked 1/4 S 33 B T.