

County Surveyor's Record, Douglas County, Oregon

5963
X

Subdivisions, T. 29 S., R. 7 W.

CHAINS

A fir, 16 ins. diam., bears N.60*W., 9 lks. dist.,
marked $\frac{1}{4}$ S 28 B T.

Thence from the $\frac{1}{4}$ sec. cor.

S.89*01'E., bet. secs. 28 and 33.

Ascend over NW. slope, 360 ft.

3.80 Road, bears NW. and S.

21.20 Top of spur, slopes NW.; descend N. and NE. slope, 161 ft.

30.70 Head of draw, course N.

36.10 Draw, course NW.; ascend W. slope, 98 ft.

38.87 Intersect the point for cor. of secs. 27, 28, 33, and 34,
located by measurement from the original bearing trees.

At the exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
the ground, for cor. of secs. 27, 28, 33, and 34, with
brass cap marked

T29S:R7W
S28:S27
S33:S34
1924

from which (the original bearing trees)

A laurel, 30 ins. diam., bears N.32*E., 36 lks. dist.
(not N.47*E.)

A laurel, 24 ins. diam., bears S.46*E., 23 lks. dist.,
remarked T 29 S R 7 W S 34 B T.

A laurel, 22 ins. diam., bears S.80*W., 50 lks. dist.,
(not S.78*W.), remarked T 29 S R 7 W S 33 B T.

An oak stump, bears N.47*W., 23 lks. dist. (not N.
37*W., 13 lks.), blazes are plain on the stump.

New bearing trees:

A fir, 6 ins. diam., bears N.24*E., 14 lks. dist.,
marked T 29 S R 7 W S 27 B T.

A cedar, 14 ins. diam., bears N.70*W., 41 lks. dist.,
marked T 29 S R 7 W S 28 B T.

Land, rolling.

Soil, clay loam, 2nd rate.

Timber, fir, laurel, cedar, and pine.

Undergrowth, hazel, fir, and laurel.