

## CHAINS

S.0\*30\*W., bet. secs. 33 and 34.

Over rolling land, through heavy timber and dense undergrowth.

Descend gradual SW. slope.

- 2.00 Head of draw, course NW.; ascend over NW. slope, 144 ft.  
 11.15 Top of Spur, slopes NW.; descend along W. slope, 14 ft.  
 14.60 Draw, course NW.; ascend N. slope, 110 ft.  
 18.35 Top of spur, slopes NW.; descend 7 ft along W. slope.  
 24.90 Draw, small spring branch, course NW.; ascend over NW. slope, 348 ft.  
 38.55 Intersect the point for  $\frac{1}{4}$  sec. cor., located by record bearing and distance from the original NE. bearing tree.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked  
 $\frac{1}{4}$   
 S33:S34  
 1924

from which (the original bearing trees)

A black oak, 12 ins. diam., bears N.77\*E., 22 lks. dist., marks are legible.

An oak stump, bears S.70\*W., 19 lks. dist.

New bearing trees:

A fir, 6 ins. diam., bears N.15 $\frac{1}{2}$ \*E., 22 lks. dist., marked  $\frac{1}{4}$  S 34 B T.

A fir, 26 ins. diam., bears N.81\*W., 54 lks. dist., marked  $\frac{1}{4}$  S 33 B T.

Thence from the  $\frac{1}{4}$  sec. cor.

S.7\*52\*W., bet. secs. 33 and 34.

Ascend NW. slope, 95 ft.

- 4.15 Top of ridge, bears NE. and SW.; descend SE. slope, 30 ft.  
 9.10 Head of draw, course SE.; thence along E. slope.  
 17.05 Top of spur, slopes SE.; descend S. slope, 250 ft.  
 27.38 Intersect the S. bdy. of the Tp., at the cor. of secs. 33 and 34, hereafter described.

Land, rolling.