

CHAINS

Soil, clay loam, 2nd rate.  
Timber, fir, oak, laurel, cedar, and pine.  
Undergrowth, hazel, laurel, and fir.

From the cor. of secs. 27, 28, 33, and 34.

S.88°35'E., bet. secs. 27 and 34.

Over rolling land, through heavy timber and dense undergrowth.

Ascend NW. slope, 154 ft.

9.00 Top of spur, slopes N.20°W.; descend NE. slope, 153 ft.

16.90 Draw, spring branch, course NW.; ascend NW. slope, 372 ft.

19.75 Cabin, bears North, 25 lks. dist.

33.70 Top of spur, slopes NW.; descend NE. slope, 92 ft.

38.30 Intersect the point for  $\frac{1}{4}$  sec. cor., located by measurement from the original bearing trees.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$$\frac{1}{4} \frac{S27}{S34}$$

1924

from which (the original bearing trees)

A fir, 30 ins. diam., bears N.20°W., 14 lks. dist., marks plain on the bark.

A fir snag, 30 ins. diam., bears S.23°E., 23 lks. dist. (not 33 lks.), marks plain on the bark.

New bearing trees:

A fir, 12 ins. diam., bears S.38 $\frac{1}{2}$ °E., 116 lks. dist., marked  $\frac{1}{4}$  S 34 B T.

A fir, 12 ins. diam., bears N.78°W., 7 lks. dist., marked  $\frac{1}{4}$  S 27 B T.

Thence from the  $\frac{1}{4}$  sec. cor.

N.89°06'E. bet. secs. 27 and 34.

Descend over NE. slope, 118 ft.

6.10 Creek, 5 lks. wide, course NW.; ascend over SW. slope, 575 ft.

28.15 Top of spur, slopes NW.; ascend along N. slope.