

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 29 S., R. 7 W.

3967

K

CHAINS

At the point of intersection

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 26 $\frac{1}{2}$  and 34 $\frac{1}{2}$ , with brass cap marked

:T29S  
:S26 $\frac{1}{2}$   
S34 :S34 $\frac{1}{2}$   
:R7W  
1924

from which

A fir, 12 ins. diam., bears N.43\*E., 50 lks. dist., marked T 29 S R 7 W S 26 $\frac{1}{2}$  B T.

A fir, 12 ins. diam., bears S.42\*E., 32 lks. dist., marked T 29 S R 7 W S 34 $\frac{1}{2}$  B T.

16.70 Top of ridge, bears E. and SW.; descend SE. slope, 485 ft.

37.75 Intersect the point for  $\frac{1}{4}$  sec. cor., located by measurement from the original bearing trees.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of Sec. 34 only, with brass cap marked

$\frac{1}{4}$ S34:  
1924

from which (the original bearing trees)

A hollow black oak stump, 8 ins. diam., bears S.58\*W., 19 lks. dist. (not S.60\*W.), marks plain inside on overgrowth.

A fir, 8 ins. diam., bears N.75\*E., 11 lks. dist., marks plain on the bark.

New bearing trees:

A fir, 36 ins. diam., bears S.30\*W., 22 lks. dist., marked  $\frac{1}{4}$  S 34 B T.

A fir, 16 ins. diam., bears N.32\*W., 10 lks. dist., marked  $\frac{1}{4}$  S 34 B T.

Thence from the  $\frac{1}{4}$  sec. cor.

S.6\*06'W., along the E. bdy. of sec. 34.

Descend SE. slope, 135 ft.

4.15 Draw, course SW.; ascend N.W. slope, 27 ft.

7.20 Point of spur, slopes W.; descend SW. slope, 38 ft.