

Subdivisions, T. 29 S., R. 7 W.

CHAINS

- 8.94 A point West from the $\frac{1}{4}$ sec. cor. of secs. $34\frac{1}{2}$ and 35 hereafter described.
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. $34\frac{1}{2}$ only, with brass cap marked
- : $\frac{1}{4}$ S $34\frac{1}{2}$
1924
- from which
- A fir, 8 ins. diam., bears N.37*E., 32 lks. dist., marked $\frac{1}{4}$ S $34\frac{1}{2}$ B T.
- A fir, 10 ins. diam., bears S.34*E., 32 lks. dist., marked $\frac{1}{4}$ S $34\frac{1}{2}$ B T.
- 9.80 Draw, course SW.
- 10.90 Draw, course W.; ascend NW. slope, 241 ft.
- 22.00 Top of ridge, bears S.60*W. and E.; train along top; descend SE. slope, 146 ft.
- 29.00 Intersect the S. bdy. of the Tp., at the cor. of secs. 34 and $34\frac{1}{2}$, hereafter described.
- Land, rolling.
- Soil, clay loam, 2nd rate.
- Timber, fir, laurel, oak, pine, and cedar.
- Undergrowth, fir, hazel, and laurel.
-
- From the cor. of secs. 27 and 34, on the W. bdy. of sec. $26\frac{1}{2}$,
- N.0*17*W., along the E. bdy. of sec. 27.
- Over mountainous land, through heavy timber and dense undergrowth.
- Descend over NW. slope, 111 ft.
- 3.85 Draw, course W.; trail, bears E. and W.; ascend SW. slope, 68 ft.
- 13.65 Point of spur, slopes W.; descend NW. slope, 32 ft.
- 15.60 Head of draw, course W.; ascend SW. slope, 123 ft.
- 25.45 Top of ridge, bears NW. and SE.; spur, slopes N.30*E.; descend NW. slope, 345 ft.
- 32.72 Point for $\frac{1}{4}$ sec. cor. of sec. $26\frac{1}{2}$. West 7.04 chs. from the $\frac{1}{4}$ sec. cor. bet. secs. 26 and $26\frac{1}{2}$, hereafter