

Subdivisions, T. 29 S., R. 7 W.

CHAINS

:T29S  
 LS23  
 S27 :S26½  
 :R7W  
 1924

from which

A fir, 16 ins. diam., bears N.30½°E., 183 lks. dist.,  
 marked T 29 S R 7 W S 23 B T.

A fir, 6 ins. diam., bears S.45°E., 249 lks. dist.,  
 marked T 29 S R 7 W S 26½ B T.

74.77 Intersect the point for Ford's cor. of secs. 22, 23, 26,  
 and 27, located by measurement from the original  
 bearing trees.

At the exact cor. point,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in  
 the ground, for cor. of secs. 22 and 27, on the W. bdy.  
 of sec. 23, with brass cap marked

T29S:  
 S22:S23  
 S27:  
 R7W:  
 1924

from which (the original bearing trees)

A cedar snag, bears S.50°W., 21 lks. dist., marks  
 plain.

A fir, up rooted, bears S.13°E., 20 lks. dist.,  
 blazes are plain on the log.

A fir stump hole, bears N.45°E., 14 lks. dist.,

New bearing trees:

A fir, 22 ins. diam., bears S.70°W., 66 lks. dist.,  
 marked T 29 S R 7 W S 27 B T.

A fir, 12 ins. diam., bears N.81°W., 31 lks. dist.,  
 marked T 29 S R 7 W S 22 B T.

Land, mountainous.

Soil, clay loam, 2nd rate.

Timber, fir, laurel, oak, pine, and cedar.

Undergrowth, fir, hazel, and laurel.

N.0°15'E., along the E. bdy. of sec. 22.