

County Surveyor's Record, Douglas County, Oregon

5971

Subdivisions, T. 29 S., R. 7 W.

CHAINS	<p>Over mountainous land, through heavy timber and dense undergrowth.</p> <p>Ascend over SE. slope, 556 ft.</p>
10.50	Enter pine opening, bears E. and W.
16.00	Top of spur, slopes SW.; ascend along W. slope, changing to SE.
26.60	Top of ridge, bears NE. and SW.; descend NW. slope, 264 ft.
29.60	Leave pine opening, bears NE. and SW.; enter heavy timber and dense undergrowth.
37.95	<p>A point 40.00 chs. N. of the cor. of secs. 23 and 26$\frac{1}{2}$.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, surrounded by a mound of stone, for $\frac{1}{4}$ sec. cor. of sec. 23 only, with brass cap marked</p> <p style="text-align: right;">: $\frac{1}{4}$S23 1924</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N.76*E., 39 lks. dist., marked $\frac{1}{4}$ S 23n B T.</p> <p style="padding-left: 40px;">A fir, 36 ins. diam., bears S.36*E., 36 lks. dist., marked $\frac{1}{4}$S 23 B T.</p>
38.65	Small draw, course NW.; continue descent.
39.93	<p>Proportionate distance</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 22 only, with brass cap marked</p> <p style="text-align: right;">: $\frac{1}{4}$S22: 1924</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S.23*W., 72 lks. dist., marked $\frac{1}{4}$ S 22 B T.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N.56*W., 42 lks. dist., marked $\frac{1}{4}$ S 22 B T.</p> <p>Descend NW. slope, 160 ft.</p>
46.50	Small draw, course NW.; ascend along W. slope, 15 ft.
48.60	Point of spur, slopes NW.; descend N. slope, 136 ft.
52.05	Descend gradual NW. slope.
71.45	Creek, 5 lks. wide, course S.70*W.; trail, bears NE.