

## County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 29 S., R. 7 W.

CHAINS  
87.14

Intersect the Campbell cor. of secs. 13, 14, 23, and 24, which is a cedar post, 4 ins. sq., 12 ins. above ground, firmly set, marked T 29 S S 13 on NE., R 7 W S 24 on SE., S 23 on SW., and S 14 on NW. face, with 3 notches on S. and 1 notch on E. edge; from which (the original bearing trees)

A fir, 32 ins. diam., bears S.67 $\frac{1}{2}$ \*E., 46 lks. dist., marked T 29 S R 7 W S 24 B T.

A fir, 32 ins. diam., bears S.73\*W., 28 lks. dist., marked T 29 S R 7 W S 23 B T.

A fir, 22 ins. diam., bears N.13\*W., 52 lks. dist., marked T 29 S R 7 W S 14 B T.

Old NE. bearing tree dead and fallen; I mark

A fir, 20 ins. diam., bears N.33\*E., 68 lks. dist., marked T 29 S R 7 W S 13 B T.

Raise a mound of stone around the cor. post.

Land, rolling.

Soil, clay loam, 2nd rate.

Timber, fir, cedar, pine, laurel, and oak.

Undergrowth, vinemaple, hazel, fir, and laurel.

From the cor. of secs. 13, 14, 23, and 24, the  $\frac{1}{4}$  sec. cor. bet. secs. 13 and 24, established by Campbell, bears S.88\*03'E., 44.01 $\frac{1}{2}$  chas. dist., and is a cedar post 3 ins. sq., 12 ins. above ground, firmly set, marked  $\frac{1}{4}$  S 13 on N. and S 24 on S. face; from which

A fir, 14 ins. diam., bears N.14\*E., 70 lks. dist., marked  $\frac{1}{4}$  S 13 B T.

A laurel, 18 ins. diam., bears S.24\*W., 82 lks. dist., marked  $\frac{1}{4}$  S 24 B T.

Also,

the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., bears S.88\*03'E., 88.03 chs. This is not the original Ford cor. and is a fir, post, 4 ins. sq., 12 ins. above ground, properly marked; from which