

County Surveyor's Record, Douglas County, Oregon

5977

Subdivisions, T.29 S., R. 7 W.

CHAINS	<p>A fir, 20 ins. diam., bears S.76*W., 35 lks. dist., marked T 29 S R 7 W S 34$\frac{1}{2}$ B T.</p> <p>A fir, 12 ins. diam., bears N.55*W., 72 lks. dist., marked T 29 S R 7 W S 26$\frac{1}{2}$ B T.</p> <p>Thence</p> <p>N.0*08*W., on a true line, bet. secs. 26 and 26$\frac{1}{2}$.</p> <p>Over mountainous land, through heavy timber and dense undergrowth.</p> <p>Descend NW. slope, 266 ft.</p>
2.31	<p>Intersect the cor. established by Campbell for secs.27 and 34, being an erroneous restoration of the cor. of secs. 26, 27, 34, and 35 of Ford's survey, which cor. is a conglomerate stone, 5x12x10 ins. above ground, marked and witnessed as described by Campbell, except that the SW. bearing tree is dead. I obliterate the marks on cor. and bearing trees and re-mark the cor. W P; from which</p> <p>(New bearing tree) A fir, 32 ins. diam., bears S.3* W., 23 lks. dist., marked W P B T.</p> <p>(Old bearing tree) A fir, 12 ins. diam., bears N.2$\frac{1}{2}$* W., 47 lks. dist., re-marked W P B T.</p>
4.85	Draw, course NW.; trail, bears NW. and SE.
7.70	Point of spur, slopes NW.
12.70	Trail, bears E. and W.
14.45	Head of draw, course W.; ascend SW.slope, 175 ft.
24.40	Top of ridge, bears NW. and SE.; Descend NE. slope, 395 ft.
38.20	Head of Draw, course NE.
39.99 $\frac{1}{2}$	<p>Proportionate distance.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground. for $\frac{1}{4}$ sec. cor., with brass cap marked</p> <p style="text-align: center;">S26$\frac{1}{2}$:S26 1924</p> <p>from which</p> <p>A fir, 20 ins. diam., bears N.29*E., 38 lks. dist., marked $\frac{1}{4}$ S 26 B T.</p>