

County Surveyor's Record, Douglas County, Oregon

Metes and Bounds Survey of Tract No. 47,
T. 29 S., R. 7 W.

CHAINS

Thence

N.88°52'W., along the N. bdy. of this tract, on the N. bdy. of the Tp.

0.99 Intersect the E. bdy, of T. 28 S., R. 8 W., at the re-survey cor. of Tps. 28 and 29 S., R. 7 W., heretofore described.

2.45 Intersect cor. No. 2 of this survey, identical with cor. No. 3 of Tract No. 63, T. 28 S., R. 7 W., heretofore described.

Thence

S.0°34'W., along the W. bdy. of this tract, on the original W. bdy. of Sec. 6.

17.54 Intersect the S. bdy. of T. 28 S., R. 8 W., 1.63 chs. S.89°38'W. from the cor. of Tps. 28 and 29 S., R. 8 W., heretofore described.

21.68 Point for N. 1/16 sec. cor., on the W. bdy. of original sec. 6, T. 29 S., R. 7 W.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for cor. No. 3 of this survey, identical with cor. No. 2 of Tract No. 48, with brass cap marked

:TR 47
:AP 3
:AP 2
:TR 48
1924

Thence

S.89°19'E. (theoretical bearing of the center latitudinal subdivision line of the NW $\frac{1}{4}$ Sec. 6), bet. Tracts Nos. 47 and 48.

1.67 Intersect the E. bdy. of T. 29 S., R. 8 W., 4.08 chs. South from the cor. of Tps. 28 and 29 S., R. 8 W.

2.47 Intersect the W. bdy. of the Wm. McCullough Donation Land Claim No. 37, N.0°30'E., 21.64 chs. from the SW. cor. thereof, heretofore described.

At the point of intersection

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for cor. No. 4 of this survey, identical with cor. No. 1 of Tract No. 48, with brass cap marked