

County Surveyor's Record, Douglas County, Oregon

5993

Metes and Bounds Survey of Tract No. 50,
T. 29 S., R. 7 W.

CHAINS

S.0°03'W., along the W. bdy. of Tract No. 50 on the W. bdy. of original sec. 18.

6.93 Intersect the line bet. secs. 12 and 13, T. 29 S., R. 8 W., 2.73 chs. N.89°37'W. from the cor. of secs. 12 and 13, on the E. bdy. of the Tp.

19.89 Intersect the point for the Ford $\frac{1}{4}$ sec. cor. of secs. 13 and 18, located by measurement from the original bearing trees, as follows:

A black oak, 30 ins. diam., bears N.73°E., 112 lks. dist.

A black oak,, 24 ins. diam., bears N.0°30'W., 105 lks. dist. (not N.3°W., 1005 lks.), marks are grown over and not opened.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for cor. No. 3 of this survey, identical with cor. No. 2 of Tract No. 51, with brass cap marked

:Tr 50
:AP 3
:AP 2
:TR 51
1924

from which

A black oak, 16 ins. diam., bears N.28°E., 42 lks. dist., marked A P 3 TR 50 B T.

A pine, 6 ins. diam., bears S.13°E., 86 lks. dist., marked A P 2 TR 51 B T.

Thence

S.81°54'E., bet. Tracts Nos. 50 and 51, along the center latitudinal subdivision line of original sec. 18.

2.78 Intersect the E. bdy. of T. 29 S., R. 8 W., at resurvey $\frac{1}{4}$ sec. cor. of sec. 18 only, T. 29 S., R. 7 W., hereafter described.

25.30 Point for W. $\frac{1}{16}$ sec. cor. of original sec. 18.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for cor. No. 4 of this survey, identical with cor. No. 1 of Tract No. 51, with brass cap marked