

County Surveyor's Record, Douglas County, Oregon

5995
163

Metes and Bounds Survey of Tract No. 51,
T. 29 S., R. 7 W.

CHAINS

with cor. No. 2 of Tract No. 52, with brass cap marked

:TR 51
:AP 3
:AP 2
:TR 52
1924

from which

A fir, 8 ins. diam., bears N.12°E., 49 lks. dist.,
marked A P 3 TR 51 B T.

A cedar, 7 ins. diam., bears S.60°E., 6 lks. dist.,
marked A P 3 TR 51 B T.

Thence

S.78°26'E., bet. Tracts Nos. 51 and 52, along the south
latitudinal subdivision line of original sec. 18.

2.86 Intersect the E. bdy. of T. 29 S., R. 8 W., 7.09 chs.

N.0°03'W. from the $\frac{1}{2}$ sec. cor. of sec. 13 only, here-
after described.

25.50 Point for SW. 1/16 sec. cor. of original sec. 18.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in
the ground, for cor. No. 4 of this survey, identical
with cor. No. 1 of Tract No. 52, with brass cap marked

TR 51:
AP 4:SW 1/16
AP 1:
TR 52:SW 1/16
1924

from which

A fir, 12 ins. diam., bears N.39°W., 20 lks. dist.,
marked A P 4 TR 51 B T.

A black oak, 24 ins. diam., bears S.83°W., 20 lks.
dist., marked A P 1 TR 52 B T.

Thence

N.0°23'E., along the E. bdy. of Tract No. 51, on the
west meridional subdivision line of original sec. 18.

20.66 Intersect cor. No. 1 of this survey, identical with cor.

No. 4 of Tract No. 50, and the place of beginning.