

## County Surveyor's Record, Douglas County, Oregon

Metes and Bounds Survey of Tract No. 53,  
T. 29 S., R. 7 W.

## CHAINS

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for cor. No. 2 of this survey, with brass cap marked

:AP 2  
:TR 53  
1924

from which

A black oak, 52 ins. diam., bears S.66\*E., 71 lks. dist., marked A P 2 TR 53 B T.

Thence

S.1\*18'W., along the W. bdy. of Tract No. 53, on W. bdy. of original sec. 30.

19.09 Point for N. 1/16 sec. cor. on the W. bdy. of original sec. 30.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for cor. No. 3 of this survey, identical with cor. No. 2 of Tract No. 54, with brass cap marked

:TR 53  
:AP 3  
:AP 2  
:TR 54  
1924

from which

A cedar, 24 ins. diam., bears N.85\*E., 25 lks. dist., marked A P 3 TR 53 B T.

A cedar, 6 ins. diam., bears S.20\*E., 18 lks. dist., marked A P 2 TR 54 B T.

Thence

S.80\*16'E., bet. Tracts Nos. 53 and 54, along the north latitudinal subdivision line of original sec. 30.

2.60 Intersect E. bdy. of T. 29 S., R. 8 W., 12.54 chs. N.0\*15'E. from the cor. of secs. 24 and 25.

23.61 Point for NW. 1/16 sec. cor. of original sec. 30.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for Cor. No. 4 of this survey, identical with cor. No. 1 of Tract No. 54, with brass cap marked