

County Surveyor's Record, Douglas County, Oregon

6001
169

Metes and Bounds Survey of Tract No. 55,
T. 29 S., R. 7 W.

CHAINS

E $\frac{1}{2}$ SW $\frac{1}{4}$, SW $\frac{1}{4}$ SW $\frac{1}{4}$ Sec. 30, H.E. 13367, Feb. 12, 1904, F.C. 02249 issued to Wesley Lamb Nov. 10, 1908. Patented to Heirs, 125.87 acres

Fractional SW $\frac{1}{4}$ SW $\frac{1}{4}$ original sec. 30.

I commence at Cor. No. 4 of this survey, identical with the W. 1/16 sec. cor. bet. original secs. 30 and 31, heretofore described.

Thence

N.0*59'E., along the E. bdy. of Tract No. 55, on the west meridional subdivision line of original sec. 30.

20.95 Point for SW. 1/16 sec. cor. of original sec. 30.

Set an iron post, 3 ft, long, 1 in. diam., 28 ins. in the ground, for cor. No. 1 of this survey, with brass cap marked

S30
AP 1:SW 1/16
TR 55:
1924

from which

A laurel, 34 ins. diam., bears S.74*W., 53 lks. dist., marked A P 1 TR 55 B T.

Thence

N.75*01'W., along the N. bdy. of Tract No. 55, on the south latitudinal subdivision line of original sec. 30.

21.15 Intersect the E. bdy. of T. 29 S., R. 8 W., 14.06 chs.

N.0*23'E. from the $\frac{1}{4}$ sec. cor. of sec. 25 only.

24.59 Point for S. 1/16 sec. cor. on W. bdy. of original sec. 30.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for cor. No. 2 of this survey, with brass cap marked

:AP 2
:TR 55
1924

from which

A fir, 28 ins. diam., bears S.16'E., 53 lks. dist., marked A P 2 TR 55 B T.

Thence

S.1*49'W., along the W. bdy. of Tract No. 55, on the W.