

Metes and Bounds Survey of Tract No. 55,  
T. 29 S., R. 7 W.



CHAINS

bdy. of original sec. 30.

18.66 Intersect the point for Ford's cor. of secs. 25, 30, 31, and 36, located by measurement from the stump holes of the original bearing trees. The bearing trees have completely rotted away.

At the cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for cor. No. 3 of this survey, with brass cap marked

:TR 55  
:AP 3

1924

from which

A fir, 20 ins. diam., bears N.46°E., 21 lks. dist., marked A P 3 TR 55 B T.

Thence

S.69°57'E., along the S. bdy. of Tract No. 55, on the original line bet. secs. 30 and 31.

4.12 Intersect the E. bdy. of T. 29 S., R. 8 W., at the re-survey cor. of secs. 30 and 31, T. 29 S., R. 7 W., hereafter described.

25.40 Intersect cor. No. 4 of this survey and the place of beginning.

North Bdy. T. 29 S., R. 8 W.  
(Hathorn Survey)

Retracement

From the original Hathorn cor. of Tps. 28 and 29 S., Rs. 7 and 8 W.

S.89°46'W., retracing the line bet. secs. 1 and 36.

39.96 The 1/4 sec. cor., bears South, 9 lks. dist.

79.98 Fall 8 lks. S. of the cor. of secs. 1, 2, 35, and 36.

From the Hathorn cor. of Tps. 28 and 29 S., Rs. 7 and 8 W., now the cor. of Tps. 28 and 29 S., R. 8 W., hereafter described.

S.89°38'W., bet. secs. 1 and 36.

Over rolling land, through heavy timber and dense undergrowth.