

County Surveyor's Record, Douglas County, Oregon

6007

East Bdy. T. 29 S., R. 8 W.
(Hathorn Survey)

CHAINS
36.24

Coos Bay Highway, bears NE. and SW.

36.61 Wire fence, bears NE. and SW.; enter grain field.

36.62 As the true point for $\frac{1}{4}$ sec. cor. of sec. 1 only falls in cultivated grain field where it is impracticable to establish a permanent cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness cor. to the $\frac{1}{4}$ sec. cor. of sec. 1 only, with brass cap marked

$\frac{1}{4}$ S1:
WC
1924

from which

A white oak, 36 ins. diam., bears N.38 $\frac{1}{4}$ *W., 411 lks. dist., marked W C $\frac{1}{4}$ S 1 B T.

No other bearing tree or other object available, no stones available for mound.

40.00 Point for $\frac{1}{4}$ sec. cor. of sec. 1 only in grain field.

47.50 Leave grain field, bears E. and W.; ascend gradually, 63 ft.

52.00 Picket fence, bears NW. and SE.

58.00 Granary on line.

61.50 Ireland's house on line.

62.30 Wire fence, bears E. and W.

65.00 Road, bears E. and W.

65.26 Intersect the line bet. secs. 6 and 7, T. 29 S., R. 7 W., 1.80 chs. S.89*28'E., from the Ford cor. of secs. 1, 6, 7, and 12, restored as witness point, heretofore described.

At the point of intersection

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 6 and 7, T. 29 S., R. 7 W., with brass cap marked

:T29S
:S6
:S7
:R7W
1924

from which