

County Surveyor's Record, Douglas County, Oregon

East Bdy. T. 29 S., R. 8 W.  
(Hathorn Survey)

CHAINS

trees and are not opened, blazes are plain.

At the exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs, 12 and 13 only, with brass cap marked

T29S:  
S12:  
S13:  
R8W:  
1924

from which (the original bearing trees)

A black oak, 20 ins. diam., bears N.59\*E., 39 lks. dist.,

A black oak, 40 ins. diam., bears S.45\*E., 77 lks. dist.

A black oak, 24 ins. diam., bears S.4\*W., 223 lks. dist.

A black oak, 14 ins. diam., bears N.4\*W., 94 v lks. dist.

New bearing trees:

A black oak, 14 ins. diam., bears S.57\*W., 62 lks. dist., marked T. 29 S R 8 W S 13 B T.

A black oak, 12 ins. diam., bears N.5\*W., 34 lks. dist., marked T 29 S R 8 W S 12 B T.

Land, rolling.

Soil, clay loam, 2nd rate.

Timber, oak and fir.

Undergrowth, oak, fir, hazel, and maple.

S.0\*03'E., along the E. bdy. of sec. 13.

Ascend 15 ft. through scattering <sup>oak</sup> timber.

2.50 Descend over SW. slope, 655 ft.

12.90 Top of spur, slopes SW.

13.33 Intersect the center latitudinal subdivision line of sec.

18, T. 29 S., R. 7 W., S.81\*54'E., 2.78 chs. from the Ford  $\frac{1}{2}$  sec. cor. of secs. 13 and 18, restored as cor. No. 3 of Tract No. 50, identical with Cor. No. 2 of Tract No. 51, heretofore described.

At the point of intersection