

County Surveyor's Record, Douglas County, Oregon

8015

East Bdy. T. 29 S., R. 8 W.
(Hathorn Survey)

CHAINS

39.97 Intersect the point for Hathorn's $\frac{1}{4}$ sec. cor. of secs. 19 and 24, located by measurement from the original bearing trees on which the marks are legible.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 24 only, with brass cap marked

$\frac{1}{4}$ S24:
1924

*FD. OK 1/10/80
H. JOHNSON
M 81-75*

from which (the original bearing trees)

A laurel, 20 ins. diam., bears S.81*E., 20 lks. dist.,

A laurel, 18 ins. diam., bears N.12*W., 30 lks. dist.,

New bearing trees:

A fir, 20 ins. diam., bears S.5*W., 37 lks. dist.,
marked $\frac{1}{4}$ S 24 B T.

A fir, 10 ins. diam., bears N.69*W., 32 lks. dist.,
marked $\frac{1}{4}$ S 24 B T.

Thence from the $\frac{1}{4}$ sec. cor.

S.0*15'W., along the E. bdy. of sec. 24.

Ascend NW. slope, 45 ft.

4.55 Top of ridge, bears NE. and SW.; descend SE. slope, 597 ft.

8.05 Intersect the line bet. secs. 19 and 30, T. 29 S., R. 7 W., S.80*27'E., 2.24 chs. from Ford's cor. of secs. 19, 24, 25, and 30, restored as cor. No. 2 of Tract No. 53, heretofore described.

At the point of intersection

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for resurvey cor. of secs. 19 and 30, T. 29 S., R. 7 W., with brass cap marked

:T29S
:S19

:S30
:R7W
1924

from which

A pine, 14 ins. diam., bears N.32*E., 38 lks. dist.,
marked T 29 S R 7 W S 19 B T.

A cedar, 10 ins. diam., bears S.55*E., 20 lks. dist.,
marked T 29 S R 7 W S 30 B T.