

County Surveyor's Record, Douglas County, Oregon

East Bdy. T. 29 S., R. 8 W.
(Hathorn Survey)

CHAINS

S.0*23'W., along the E. bdy. of sec. 25.

Over rolling land, through heavy timber and dense undergrowth.

Ascend N. slope, 58 ft.

1.95 Top of spur, slopes, N.60*E.; descend along E. slope, 234 ft.

5.85 Top of spur, slopes SE.; descend SW. slope.

6.60 Intersect the center latitudinal subdivision line of original sec. 30, T. 29 S., R. 7 W., S.80*06'E., 2.90 chs. from the Ford $\frac{1}{4}$ sec. cor. of secs. 25 and 30, restored as cor. No. 3 of Tract No. 54, heretofore described.

At the point of intersection

Set an iron post 3 ft. long, 1 in. diam., 28 ins. in the ground, for resurvey $\frac{1}{4}$ sec. cor. of sec. 30 only, T. 29 S., R. 7 W., with brass cap marked

$\frac{1}{4}$ S30
1924

from which

A fir, 26 ins. diam., bears N.17*E., 76 lks. dist., marked $\frac{1}{4}$ S 30 B T.

A fir, 30 ins. diam., bears S.20*E., 41 lks. dist., marked $\frac{1}{4}$ S 30 B T.

13.25 Creek, 3 lks. wide, course N.60*E.; ascend NE. slope. 137 ft.

17.35 Top of spur, slopes E.; descend SE. slope, 115 ft.

25.64 Intersect the N.bdy. of Tract No. 55, S.75*01'E., 3.44 chs. from cor. No. 2 thereof, heretofore described.

26.10 Draw, course E.; ascend NE. slope, 150 ft.

39.70 Intersect the point for Hathorn's $\frac{1}{4}$ sec. cor. of secs. 25 and 30, located by measurement from the original bearing trees, on the bark of which the marks are plain.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 25 only, with brass cap marked

$\frac{1}{4}$ S25:
1924