

County Surveyor's Record, Douglas County, Oregon

East Bdy. T. 29 S., R. 8 W.
(Hathorn Survey)

CHAINS

from which (the original bearing trees)

A fir, 24 ins. diam., bears S.60*E., 28 lks. dist.,
(not S.63*E.)

A fir, 24 ins. diam., bears S.46*W., 31 lks. dist.,
(not S.45*W.)

New bearing trees:

A fir, 46 ins. diam., bears S.75*W., 57 lks. dist.,
marked 1/4 S 25 B T.

A fir, 36 ins. diam., bears N.67*W., 32 lks. dist.,
marked 1/4 S 25 B T.

Thence from the 1/4 sec. cor.

S.0*14'E., along the E. bdy. of sec. 25.

Descend SE. slope, 70 ft.

5.11 Intersect the line bet. secs. 30 and 31, T.29 S., R. 7
W., S.69*57'E., 4.12 chs. from the Ford cor. of secs.
25, 30, 31, and 36, restored as cor. No. 3 of Tract No.
55, heretofore described.

At the point of intersection

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
the ground, for resurvey cor. of secs. 30 and 31, T.
29 S., R. 7 W., with brass cap marked

::T29S
:S30
:S31
:R7W
1924

from which

A fir, 10 ins. diam., bears N.40*E., 36 lks. dist.,
marked T 29 S R 7 W S 30 B T.

A fir, 12 ins. diam., bears S.19*E., 51 lks. dist.,
marked T 29 S R 7 W S 31 B T.

9.92 Head of draw, course NE.; trail, bears NE. and SW.;
ascend NE. slope, 28 ft.

12.40 Top of ridge at low saddle, bears NW. and SE.; trail
along top; descend SW. slope, 33 ft.

15.70 Draw, course SW.; ascend NW. slope, 158 ft.

25.50 Top of spur, slopes SW.; descend S. slope, 60 ft.

28.35 Draw, course SW.; ascend N. slope, 15 ft.