

County Surveyor's Record, Douglas County, Oregon

6021

East Bdy. T. 29 S., R. 8 W.
(Hathorn Survey)

CHAINS	<p>A fir, 10 ins. diam., bears N.15*W., 14 lks. dist., marked $\frac{1}{4}$ S 36 B T.</p> <p>Thence from the $\frac{1}{4}$ sec. cor. S.0*24*W., along the E. bdy. of sec. 36.</p> <p>Descend SE. slope, 586 ft.</p> <p>10.43 Intersect the S. bdy. of T. 29 S., R. 7 W., N.89*16'E., 5.60 chs. from the Ford cor. of Tps. 29 and 30 S., Rs. 7 and 8 W., restored as witness point, hereafter described.</p> <p>At the point of intersection</p> <p>Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, for cor. of Tps. 29 and 29$\frac{1}{2}$ S., R. 7 W., with brass cap marked</p> <div style="text-align: right; margin-left: 400px;"> <p>:T29S :R7W :S31 <hr/>:S31 :T29$\frac{1}{2}$S 1924</p> </div> <p>from which</p> <p style="padding-left: 40px;">A chinquapin, 14 ins. diam., bears N.5*E., 66 lks. dist., marked T 29 S R 7 W S 31 B T.</p> <p style="padding-left: 40px;">A chinquapin, 12 ins. diam., bears S.44*E., 54 lks. dist., marked T 29$\frac{1}{2}$ S R 7 W S 31 B T.</p> <p>28.65 Rim rock, 6 ft. high, bears NW. and SE.</p> <p>35.75 Blue Canyon Creek, 5 lks. wide, course SE., ascend NE. slope, 78 ft.</p> <p>39.96 Intersect the point for the Hathorn cor. of Tps. 29 and 30 S., R 7 and 8 W., located by measurement from the SW. original bearing tree and from the position indicated by stump holes of the NE., NW., and SE. bearing trees, all of which have been destroyed by decay.</p> <p>At the exact cor. point</p> <p>Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, for cor. of T. 29 S., R. 8 W. and T 29$\frac{1}{2}$ S., R. 7 W., with brass cap marked</p> <div style="text-align: right; margin-left: 400px;"> <p>T29S:T29$\frac{1}{2}$S R8W:R7W S36:S31 <hr/>1924</p> </div>
--------	---