

Subdivisions, T. 29 S., R. 8 W.

CHAINS

- 3.00 Draw, course N.; ascend along N. slope, 21 ft.
- 5.45 Top of spur, slopes NW.; descend W. slope, 152 ft.
- 12.90 Draw, small spring branch, course N.20*E.; ascend E. slope, 401 ft.
- 22.75 Top of spur, slopes NE.; descend along N. slope, 273 ft.
- 39.61 Intersect the point for the $\frac{1}{4}$ sec. cor., located by measurement from the original bearing trees.
- At the exact cor. point
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
- $$\frac{1}{4} \frac{S13}{S24}$$
- 1924
- from which (the original bearing trees)
- A fir, 36 ins. diam., bears N.28*W., 17 lks. dist., marks plain on the bark.
- A fir, (now dead), 32 ins. diam., bears S.59*E., 12 lks. dist., marks are on the bark.
- New bearing trees:
- A fir, 30 ins. diam., bears S.53*W., 27 lks. dist., marked $\frac{1}{4}$ s 24 B T.
- A fir, 36 ins. diam., bears N.73*W., 59 lks. dist., marked $\frac{1}{4}$ S 13 B T.
- Thence from the $\frac{1}{4}$ sec. cor.
- N.89*35'W., bet. secs. 13 and 24.
- Descend over NW. slope, 218 ft.
- 8.90 Draw, course NW.
- 13.35 Draw, course N.
- 17.25 Draw, small spring branch, course W.
- 20.45 Leave spring branch, course N.
- 22.00 Spring branch, 4 lks. wide, course NE.; ascend SE. slope, 290 ft.
- 38.00 Top of spur, slopes S.; descend SW. slope, 15 ft.
- 40.04 Intersect the point for cor. of secs. 13, 14, 23, and 24, located by measurement from the original bearing trees.
- At the exact cor. point