

County Surveyor's Record, Douglas County, Oregon

6029

Subdivisions, T. 29 S., R. 8 W.

CHAINS

Set an iron post, 3 ft. long, 2 ins diam., 28 ins. in the ground, for cor. of secs. 13, 14, 23, and 24, with brass cap marked

T29S:R8W
S14:S13
S23:S24
 1924

from which (the original bearing trees)

A laurel, 14 ins. diam., bears N.33*E., 21 lks. dist., marks grown over.

A laurel, 10 ins. diam., bears S.20*E., 16 lks. dist., marks grown over.

A laurel, 8 ins. diam., bears N.75*W., 11 lks. dist., marks grown over.

SW. bearing tree rotted down.

New bearing trees:

A cedar, 6 ins. diam., bears N.40*E., 9 lks. dist., marked T 29 S R 8 W S 13 B T.

A fir, 38 ins. diam., bears S.37*E., 48 lks. dist., marked T. 29 S R 8 W S 24 B T.

A laurel, 10 ins. diam., bears S.81*W., 46 lks. dist., marked T 29 S R 8 W S 23 B T.

A fir, 8 ins. diam., bears N.7W., 16 lks. dist., marked T 29 S R 8 W S 14 B T.

Land, rolling and mountainous.

Soil, rocky clay loam, 2nd rate.

Timber, fir, cedar, and laurel.

Undergrowth, hazel, fir, laurel, and maple.

N.0*02*W., bet. secs. 13 and 14.

Over rolling land, through heavy timber and dense undergrowth.

Ascend over S. slope, 121 ft.

- 3.65 Top of spur, slopes SE.; descend along E. slope, 37 ft.
- 9.60 Head of draw, course SE.; ascend SE. slope, 154 ft.
- 15.65 Top of spur, slopes E.; descend NE. slope, 55 ft.
- 24.20 Head of draw, course E.; ascend SE. slope, 174 ft.