

Subdivisions, T. 29 S., R. 8 W.

CHAINS

- 31.00 Top of spur, slopes E.; descend NE. slope, 282 ft.
- 39.88 Intersect the point for the $\frac{1}{4}$ sec. cor., located by measurement from the original bearing trees.
- At the exact cor. point
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
- $\frac{1}{4}$
S14:S13
1924
- from which (the original bearing trees)
- A chinquapin stump, bears S.66*E., 22 lks. dist.
- A fir, 30 ins. diam., bears S.12*W., 65 lks. dist., marks are plain on the bark.
- New bearing trees:
- A fir, 16 ins. diam., bears N.89*E., 9 lks. dist., marked $\frac{1}{4}$ S 13 B T.
- A fir, 22 ins. diam., bears N.34*W., 21 lks. dist., marked $\frac{1}{4}$ S 14 B T.
- Thence from the $\frac{1}{4}$ sec. cor.
- N.0*17'E., bet. secs. 13 and 14.
- Descend steep NE. slope, 408 ft.
- 12.40 Creek, 12 lks. wide, course SE.; thence over nearly level land.
- 13.95 Old road, bears E. and W.; ascend steep SE/ slope, 495 ft.
- 24.00 Broken cliff, 50 ft high, bears NE. and SW.
- 25.75 Top of spur, slopes SW.; ascend W. and SW. slope.
- 38.70 Small spring branch, course SW.
- 39.75 Intersect the point for cor. of secs. 11, 12, 13, and 14, where I find a stump hole indicating the position of the original cor. tree, further identified by measurement from the original bearing trees.
- At the exact cor. point
- Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 11, 12, 13, and 14, with brass cap marked
- T29S:R8W
S11:S12

S14:S13
1924