

Subdivisions, T. 29 S., R. 8 W.

CHAINS

Descend W. slope, 68 ft.

4.55 Fence, bears NW. and SE.; leave timber; enter opening.

4.60 Draw, course NW.; ascend 20 ft.

7.95 Road, bears N. and S.; descend gradually 45 ft.

8.25 A house, bears South, 1.00 ch. dist.

12.00 Fence, bears NW. and SE.

14.55 Draw, course N.; ascend E. slope, 200 ft.

16.35 Pole fence, bears N. and S.; leave opening; enter timber.

22.35 Top of spur, slopes SE.; descend along S. slope, 10 ft.

23.35 Ascend SE. slope, 226 ft.

24.60 Old fence, bears N. and S.

32.60 Top of spur, slopes NE.; descend along N. slope, 116 ft.

39.83 Intersect the point for $\frac{1}{4}$ sec. cor., located by measurement and record bearing from the original NE. bearing tree.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ $\frac{S1}{S12}$
1924

from which (original bearing tree)

A fir, 36 ins. diam., bears N.59*E., 20 lks. dist., marks are plain on the bark.

New bearing trees:

A maple, 12 ins. diam., bears S.39*E., 48 lks. dist., marked $\frac{1}{4}$ S 12 B T.

A fir, 16 ins. diam., bears N.71*W., 51 lks. dist., marked $\frac{1}{4}$ S 1 B T.

Thence from the $\frac{1}{4}$ sec. cor.

N.89*27'W., bet. secs. 1 and 12.

Ascend gradually 40 ft.

1.90 Top of ascent; descend NW. slope, 375 ft.

15.70 Draw, course NW.

21.45 Draw, course N, bottom of descent; thence over rolling N. slope.