

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 29 S., R. 8 W.

CHAINS
39.89

Intersect the point for cor. of secs. 1, 2, 11, and 12,
located by measurement from the original bearing trees.

At the exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
the ground, for cor. of secs. 1, 2, 11, and 12, with
brass cap marked

T29S:R8W
S2:S1

S11:S12
1924

from which (the original bearing trees)

A fir, 40 ins. diam., bears N.26*E., 39 lks.dist.,
marks are plain.

A cedar, 40 ins. diam., bears S.75*W., 41 lks.dist.,
plainly marked,

A fir, 12 ins. diam., bears N.15*W., 48 lks. dist.,
plainly marked (not a cedar, 40 ins. diam.,N.15*
W., 47 lks.)

New bearing tree:

A fir, 12 ins. diam., bears S.51½*E., 77 lks. dist.,
marked T 29 S R 8 W S 12 B T.

Land, rolling.

Soil, clay loam, 2nd rate.

Timber, fir, cedar, laurel, and maple.

Undergrowth, hazel, fir, and laurel.

N.0*05*W., bet. secs. 1 and 2.

Over rolling land, through heavy timber and dense under-
growth.

Descend N. slope, 50 ft.

4.80 Creek, 8 lks. wide, course SE.; thence over nearly level
land.

6.40 Coos Bay Highway, bears E. and W.

18.75 Woven wire fence, bears E. and W.

20.90 Shields Creek, 10 lks. wide, course SE.

21.40 Pole fence, bears NW. and SE.

27.75 Same creek, 10 lks. wide, course SW.