

County Surveyor's Record, Douglas County, Oregon

6037

South Bdy. T. 29 S., R. 7 W.
(Ford Survey)

CHAINS

New bearing trees:

A chinquapin, 20 ins. diam., bears N.22*E., 72 lks. dist., marked W P B T.

A fir, 30 ins. diam., bears S.20*E., 49 lks. dist., marked W P B T.

Thence

N.89*16'E., on a blank line.

5.60 Intersect the E. bdy. of T. 29 S., R. 8 W., at the cor. of Tps. 29 and 29½ S., R. 7 W., heretofore described.

Thence continue my line and measurement along the S. bdy. of Sec. 31, T. 29 S., R. 7 W.

Descend SE. slope, 320 ft. through heavy timber and dense undergrowth.

16.80 Head of draw, course SE.

27.70 Top of spur, slopes SE.; continue descent over NE. slope, 175 ft.

Leave heavy timber, enter pine opening, bears NW. and SE.

40.99 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor. of sec. 31 only, with brass cap marked

¼S31

1924

from which

A fir, 20 ins. diam., bears N.60*E., 45 lks. dist., marked ¼ S 31 B T.

A fir, 18 ins. diam., bears N.68*W., 76 lks. dist., marked ¼ S 31 B T.

Descend SE. slope, 548 ft.

42.30 Draw, course SE.

46.84 Point for ¼ sec. cor. of sec. 31, T. 29½ S., R. 7 W., later determined.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor. of sec. 31 only, T. 29½ S., R. 7 W., with brass cap marked