

South Edy. T. 29 S., R. 7 W.
(Ford Survey)

CHAINS
8.70

Intersect the cor. of secs. 32 and 33, T. 29 $\frac{1}{2}$ S., R. 7 W.,
hereafter described.

12.75 Head of draw, course N.; ascend NW. slope, 110 ft.

24.80 Top of ridge, bears SE. and SW.; spur, slopes NE.; descend E. slope, 148 ft.

35.50 Head of draw, course N.; ascend NW. slope, 40 ft.

38.00 Top of low ridge, bears N.60°E. and SW.; trail along top; thence along S. slope.

38.51 Intersect the point for $\frac{1}{4}$ sec. cor., located by measurement from the original bearing trees.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 33 only, with brass cap marked

$\frac{1}{4}$ S33

1924

from which (the original bearing trees)

A laurel, 22 ins. diam., bears N.17°W., 50 lks. dist., marks rotted away.

A laurel, 24 ins. diam., bears S.10°W., 30 lks. dist., blazes show plainly, but marks have been obliterated.

New bearing trees:

A fir, 10 ins. diam., bears N.43°E., 23 lks. dist., marked $\frac{1}{4}$ S 33 B T.

A fir, 7 ins. diam., bears N.49°W., 18 lks. dist., marked $\frac{1}{4}$ S 33 B T.

Thence from the $\frac{1}{4}$ sec. cor.

N.89°37'E., along the S. bdy. of sec. 33.

Ascend along S. slope, 30 ft.

4.15 Top of spur, slopes SE.; descend E. slope, 102 ft.

9.00 Point for $\frac{1}{4}$ sec. cor. of sec. 33, T. 29 $\frac{1}{2}$ S., R. 7 W., later determined.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 33, T. 29 $\frac{1}{2}$ S., R.