

County Surveyor's Record, Douglas County, Oregon

South Bdy. T: 29 S., R. 7 W.
(Ford Survey)

CHAINS

7 W., with brass cap marked

1/4 S 33
T 29 1/2
1924

from which

A fir, 6 ins. diam., bears S.84*E., 12 lks. dist.,
marked 1/4 S 33 T 29 1/2 B T.

A fir, 9 ins. diam., bears S.58*W., 20 lks. dist.,
marked 1/4 S 33 T 29 1/2 B T.

- 12.55 Draw, course S.; ascend SW. slope, 84 ft.
23.55 Top of spur, slopes S.20*E.; descend SE. slope, 136 ft.
29.20 Draw, course SE.; ascend SW. slope, 84 ft.
36.55 Point of spur, slopes SW.; descend SE. slope, 38 ft.
39.49 Intersect the point for cor. of secs. 3, 4, 33, and 34,
located by measurement from the original bearing trees.

At the exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
the ground, for cor. of secs. 33 and 34, with brass
cap marked

T 29 S: R 7 W
S 33: S 34

1924

from which (the original bearing trees)

A laurel, 40 ins. diam., bears N.55*E., 55 lks.
dist., (not N.65*E.), marks are obliterated.

Stump hole of a black oak, bears S.66*E., 128 lks.
dist. (not S.63*E., 138 lks.)

A black oak snag, 12 ins. diam., bears N.71*W., 29
lks. dist. (not N.65*W.)

A black oak, 14 ins. diam., bears S.48*W., 44 lks.
dist. (not S.53*W.), marks visible.

New bearing trees:

A pine, 8 ins. diam., bears N.80*E., 93 lks. dist.,
marked T 29 S R 7 W S 34 B T.

A fir, 10 ins. diam., bears N.60*W., 93 lks. dist.,
marked T 29 S R 7 W S 33 B T.

Land, rolling.

Soil, clay loam 2nd rate.