

South Bdy. T. 29 S., R. 7 W.  
(Ford Survey)

CHAINS

10.17 Point for 1/4 sec. cor. of sec. 34 only, T. 29 1/2 S., R. 7 W.,  
later determined.

Set an iron post, 3ft. long, 1 in. diam., 28 ins. in the  
ground, for 1/4 sec. cor. of sec. 34, T. 29 1/2 S., R. 7 W.,  
only, with brass cap marked

1/4 S 34  
T 29 1/2  
1924

from which

A laurel, 44 ins. diam., bears S.3\*E., 62 lks. dist.,  
marked 1/4 S 34 T 29 1/2 BT.

A laurel, 46 ins. diam., bears S.54\*W., 58 lks. dist.,  
marked 1/4 S 34 T 29 1/2 B T.

17.35 Head of draw, course SW.; ascend W. and SW. slope, 222 ft.

27.80 Top of spur, slopes S.; descend SE. slope, 56 ft.

33.70 Head of draw, course S.; ascend SW. slope, 30 ft.

35.65 Top of spur, slopes S.; descend SE. slope, 45 ft.

39.07 Intersect the point for cor. of secs. 2, 3, 34, and 35,  
located by measurement from the original bearing trees.

At the exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in  
the ground, for cor. of secs. 34 and 34 1/2, T. 29 S., R.  
7 W., with brass cap marked

T 29 S: R 7 W  
S 34: S 34 1/2  
1924

from which (the original bearing trees)

A black oak, 30 ins. diam., bears N.59\*E., 53 lks.  
dist. (not N.30\*E., 50 lks.), marks plain; opened  
overgrowth shows marks 70 years old.

A black oak, 36 ins. diam., bears S.2\*E., 153 lks.  
(not S.5\*W.), shows scar of blaze.

A black oak, 26 ins. diam., bears S.81\*W., 35 lks.  
dist. (not S.8\*E.), overgrowth opened, 70 years  
old, marks plain.

A pine stump hole, bears N.5\*W., 10 lks. dist.