

County Surveyor's Record, Douglas County, Oregon

South Bdy. T. 29 S., R. 7 W.
(Ford Survey)

CHAINS

New bearing trees:

A fir, 12 ins. diam., bears N.51*E., 23 lks. dist.,
marked T 29 S R 7 W S 34 $\frac{1}{2}$ B T.

A fir, 20 ins. diam., bears N.62*W., 42 lks. dist.,
marked T 29 S R 7 W S 34 B T.

Land, rolling and mountainous.

Soil, rocky clay loam, 2nd and 3rd rate.

Timber, fir, oak, pine, cedar, and laurel.

Undergrowth, hazel, laurel, fir, and vine maple.

S.89*23'E., along the S. bdy. of sec. 34 $\frac{1}{2}$, T. 29 S., R.
7 W.

Over rolling land, through heavy timber and dense under-
growth.

Descend SE. slope, 37 ft.

3.95 Small draw, course SW.; ascend W. slope, 76 ft.

9.30 Top of spur, slopes SW.; descend along S. slope, 76 ft.

10.84 Intersect the W. bdy. of sec. 35, T. 29 S., R. 7 W., as
surveyed by Campbell, 17.04 chs. N.0*34'W. from the
cor. of secs. 2, 3, 34, and 35, established by Byars,
hereafter described.

At the point of intersection

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in
the ground, for NE. cor. of T. 29 $\frac{1}{2}$ S., R. 7 W., with
brass cap marked

T29S:R7W
S34 $\frac{1}{2}$:S35
S34:
T29 $\frac{1}{2}$ S:
R7W:
1924

from which

A fir, 8 ins. diam., bears S.43*W., 4 lks. dist.,
marked T 29 $\frac{1}{2}$ S R 7 W S 34 B T.

A fir, 14 ins. diam., bears N.19*W., 17 lks. dist.,
marked T 29 S R 7 W S 34 $\frac{1}{2}$ B T.

Thence I continue line and measurement