

County Surveyor's Record, Douglas County, Oregon

South Bdy. T. 29 S., R. 7 W.
(Ford Survey)

CHAINS

S.89*23'E., on a blank line, through sec. 35, T. 29 S.,
R. 7 W.

40.00 Am unable to find any trace of Ford's $\frac{1}{4}$ sec. cor. of
secs. 2 and 35.

78.26 Intersect the point for Ford's cor. of secs. 1, 2, 35,
and 36, located by measurement from the original bear-
ing trees, which are as recorded.

A fir, 24 ins. diam., bears S.15*E., 50 lks. dist.,
blazes are plain.

A fir, 26 ins. diam., bears S.55*W., 10 lks. dist.,
blazes are plain.

A fir, 7 ins. diam., bears N.25*W., 12 lks. dist.,
marks plain on the bark.

A fir, bears N.50*E., 35 lks. dist., has rotted
away, but stump hole indicates position.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in
the ground, for witness point, with brass capp marked

WP
1924

from which (new bearing trees)

A fir, 12 ins. diam. bears N.51*E., 45 lks. dist.,
marked W P B T.

A fir, 30 ins. diam., bears N.10*W., 50 lks. dist.,
marked W P B T.

Land, rolling.

Soil, clay loam, 2nd rate.

Timber, fir, laurel, pine, and cedar.

Undergrowth, vine maple, laurel, and fir.

S.88*49'E., on a blank line, through sec. 35, T. 29 S.,
R. 7 W.

11.79 Intersect the line bet. secs. 35 and 36, as surveyed by
Campbell.

Thence through sec. 36.

38.47 Intersect the point for Ford's $\frac{1}{4}$ sec. cor. of secs. 1