

South Bdy. T. 29 S., R. 7 W.  
(Ford Survey)

## CHAINS

36, located by measurement from the original bearing trees, which are

A laurel, 16 ins. diam., bears N.35\*W., 25 lks. dist., marks are legible.

Stump hole of chinuapin, bears S.61\*W., 12 lks. dist.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness point, with brass cap marked

WP  
1924

from which ( the new bearing trees)

A fir, 18 ins. diam., bears N.59 $\frac{1}{2}$ \*E., 66 lks. dist., marked W P B T.

A fir, 22 ins. diam., bears N.68\*W., 47 lks. dist., marked W P B T.

Land, rolling and mountainous.

Soil, clay loam, 2nd rate.

Timber, fir, laurel, and cedar.

Undergrowth, hazel, vine maple, and laurel.

North Bdy. T. 30 S., R. 7 W.  
(Byars Survey)

Retracements

From the Hathorn cor. of Tps. 29 S., Rs. 7 and 8 W., on the N. bdy. of T. 30 S., R. 7 W.  
N.87\*59'E., retracing the N. bdy. of sec. 6; at 41.56 chs. fall 18 lks. N. of the  $\frac{1}{4}$  sec. cor., and at 81.37 chs. fall 48 lks. N. of the cor. of secs. 5, 6, 31, and 32.

N.87\*59'E., retracing the line bet. secs. 5 and 32; at 38.98 chs. fall 35 lks. S. of the  $\frac{1}{4}$  sec. cor., and at 78.48 chs. fall 38 lks. S. of the cor. of secs. 4, 5, 32, and 33.

N.87\*59'E., retracing the line bet. secs. 4 and 33; at 38.78 chs. fall 60 lks. S. of the  $\frac{1}{4}$  sec. cor., and at 78.24 chs. fall 89 lks. S. of the cor. of secs. 3, 4, 33, and 34.

N.87\*59'E., retracing the line bet. secs. 3 and 34; at 39.30 chs. fall 160 lks. S. of the  $\frac{1}{4}$  sec. cor. From the  $\frac{1}{4}$  sec. cor., East retracing the line bet. secs. 3 and 34, and at 39.96 chs. fall 35 lks. S. of the cor. of secs. 2, 3, 34, and 35.