

County Surveyor's Record, Douglas County, Oregon

North Bdy. T. 30 S., R. 7 W.
(Byars Survey)

CHAINS

5x12x6 ins. above ground, marked $\frac{1}{4}$ on N. face; from which the original bearing tree stumps:

A white oak, bears S.24* W., 27 lks. dist., blazes are plain.

A white oak, bears N.86*W., 42 lks. dist., marks B T are visible.

New bearing trees:

A pine, 32 ins. diam., bears N.34*E., 210 lks. dist., marked $\frac{1}{4}$ S 32 T 29 $\frac{1}{2}$ B T.

A fir, 8 ins. diam., bears S.12*E., 15 lks. dist. marked $\frac{1}{4}$ S 5 B T.

Thence from the $\frac{1}{4}$ sec. cor.

N.87*56'E., bet. secs. 5 and 32.

Ascend steep NW. slope, 563 ft.

18.90 Top of spur, slopes SW.; ascend along S slope.

34.75 Top of ascent on S. slope; descend 10 ft.

36.75 Foot of descent; ascend SW. slope, 30 ft.

39.48 Intersect the cor. of secs. 4, 5, 32, and 33, which is a sandstone, 8x12x6 ins. above ground, firmly set, marked with 4 notches on E. and 2 notches on W. edges; from which the original bearing trees:

A cedar, 30 ins. diam., bears N.54*E., 15 lks. dist., I re-mark T 29 $\frac{1}{2}$ S R 7 W S 33 B T.

A laurel, 24 ins. diam., bears S.15*E., 32 lks. dist. (not S.20*E.)

A cedar, rotted down, bears S.48*W., 138 lks. dist. (not a pine bearing S.42*W.)

A pine, (dead), 50 ins. diam., bears N.72*W., 106 lks. dist.

New bearing trees:

A pine, 10 ins. diam., bears S.36*W., 45 lks. dist. marked T 30 S R 7 W S 5 B T.

A pine, 14 ins. diam., bears N.20*W., 81 lks. dist. marked T 29 $\frac{1}{2}$ S R 7 W S 32 B T.

This cor. is on top of spur, slopes S.20*W.