

County Surveyor's Record, Douglas County, Oregon

6051

X

North Bdy. T. 30 S., R. 7 W.
(Byars Survey)

CHAINS	
	Land, mountainous. Soil, rocky clay loam, 2nd and 3rd rate. Timber, fir, oak, cedar, pine, and laurel. Undergrowth, hazel, fir, oak, and laurel.
	N.87*06'E., bet. secs. 4 and 33. Over mountainous land, through heavy timber and dense undergrowth.
0.40	Top of bluff, 60 ft. high, bears NE. and SW.; descend steep SE. slope, 555 ft.
21.70	Draw, course SE.; ascend along S. slope, 17 ft.
24.10	Trail, bears NE. and SW.
27.05	Top of spur, slopes SE.; descend E. slope, 90 ft.
29.60	Draw, course SE.; ascend SW. slope, 192 ft.
38.81	Intersect the $\frac{1}{4}$ sec. cor., which is a slate stone, 4x10x10 ins. above ground, firmly set, marked $\frac{1}{4}$ on N. face; from which the original bearing trees: A laurel, 18 ins. diam., bears S.19*E., 66 lks. dist., marked $\frac{1}{4}$ S B T. A laurel, 20 ins. diam., bears N.51*W., 64 lks. dist., marked $\frac{1}{4}$ S B T. I re-mark this tree $\frac{1}{4}$ S 33 T 29 $\frac{1}{2}$ B T. Thence from the $\frac{1}{4}$ sec. cor. N.87*34'E., bet. secs. 4 and 33. Ascend along S. slope, 5 ft.
1.00	Top of spur, slopes SE., descend E. slope, 407 ft.
17.90	Draw, water in pools, course SW.; ascend NW. slope, 440 ft.
22.35	Point of spur, slopes S.60*W.; ascend along S. slope.
30.05	Draw, course S.60*W.; ascend in draw.
36.00	Head of draw; ascend NW. slope.
39.47	Intersect the cor. of secs. 3, 4, 33, and 34, which is a pine post, 4 ins. sq., 12 ins. above ground, decaying, marked T 29 S R 7 W S 34 on NE., T 30 S S 3 on SE., S 4 on SW. and S 33 on NW. faces, with 3 notches on E. and W edges; from which the original bearing trees: