

North Edy. T. 30 S., R. 7 W.
(Byars Survey)

CHAINS

39.39 Intersect the point for $\frac{1}{4}$ sec. cor., located by measurement from the original bearing trees.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\begin{array}{r} S34 \\ T29\frac{1}{2} \\ \hline S3 \\ 1924 \end{array}$$

from which (the original bearing trees)

A fir, 32 ins. diam., bears S.20*E., 19 lks. dist., marked $\frac{1}{4}$ S B T. on the bark.

A pine stump, bears N.48*W., 122 lks. dist., blaze shows.

New bearing trees:

A fir, 18 ins. diam., bears S.54*E., 61 lks. dist., marked $\frac{1}{4}$ S 3 B T.

A fir, 16 ins. diam., bears N.78*W., 36 lks. dist., marked $\frac{1}{4}$ S 34 T 29 $\frac{1}{2}$ B T.

Thence from the $\frac{1}{4}$ sec. cor.

N.89*30'E., bet. secs. 3 and 34.

Ascend NW. slope 355 ft. through pine opening.

12.50 Top of spur, slopes SW.; ascend along S. slope.

20.20 Top of spur, slopes SE.; road, bears NW. and SE.; descend E. and NE. slope, 200 ft.

21.20 Leave pine opening, bears NW. and SE.; enter dense undergrowth.

34.10 Draw, water in pools, course SE.

35.25 Small draw, course S.; ascend SW. slope, 20 ft.

39.96 Intersect the cor. of secs. 2, 3, 34, and 35, heretofore described.

Land, rolling.

Soil, rocky clay loam, 2nd and 3rd rate.

Timber, fir, pine, oak, cedar, and laurel.

Undergrowth, hazel, vine maple, fir, oak, and laurel.