

Subdivisions, T. 29 $\frac{1}{2}$ S., R. 7 W.

CHAINS

21.75 Top of spur, slopes N.20*W.; descend abrupt NE. slope.

25.39 Intersect the S. bdy. of T. 29 S., R. 7 W., 8.70 chs.

S.89*25'E. from the cor. of secs. 32 and 33.

At the point of intersection

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 32 and 33, with brass cap marked

S32:S33
T29 $\frac{1}{2}$ S:R7W
1924

from which .

A fir, 28 ins. diam., bears S.30*E., 50 lks. dist., marked T 29 $\frac{1}{2}$ S R 7 W S 33 B T.

A maple, 8 ins. diam., bears S.29*W., 52 lks. dist., marked T 29 $\frac{1}{2}$ S R 7 W S 32 B T.

Land, mountainous.

Soil, rocky clay loam, 2nd and 3 rd rate.

Timber, fir, pine, laurel, and oak.

Undergrowth, hazel, laurel, and fir.

From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp.

North, bet. secs. 31 and 32.

Over rolling land, through heavy timber and dense undergrowth.

Ascend SE. slope, 115 ft.

3.60 Bluff, 60 ft. high, bears NE. and SW.

11.10 Top of ascent; thence nearly level.

16.85 Ascend SE. slope, 70 ft.

22.45 Top of spur, slopes N.60*E.; descend N. slope, 155 ft.

28.35 Intersect the S. bdy. of T. 29 S., R. 7 W., 7.64 chs.

N.88*12'E., from the cor. of secs. 31 and 32.

At the point of intersection

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 31 and 32, with brass cap marked