

County Surveyor's Record, Douglas County, Oregon

6059
X

Portion of South Bdy. of T. 29 S., R. 1 W.,
As Surveyed by Dennis Hathorn, Deputy Surveyor,
Under Contract No. 73, dated June 8, 1857.

CHAINS		
	East, on South Bdy of sec. 31.	
	Va. 19*25'E.	
3.00	Leave openings & enter thick timber C. NW. & SE.	+ 10
40.00	Set $\frac{1}{2}$ sec. post, from which	+ 50
	A fir, 10 ins. diam., bears S.88*W., 48 lks. dist.	
	A fir, 24 ins. diam., bears N.70*W., 33 lks. dist.	
76.30	Branch 5 lks. wide C. from NW.	- 75
77.60	Leave same C. SE.	
80.00	Set post corner of secs. 31, 32, 5 & 6, from which	- 20
	A fir, 10 ins. diam., bears S.57*W., 38 lks. dist.	
	A fir, 15 ins. diam., bears N.60*W., 36 lks. dist.	
	A Laurel, 12 ins. diam., bears S.74*E., 42 lks. dist.	
	A Chinquapin 8 ins. diam., bears N.75*E., 27 lks. dist.	
80.00	Va. 18*50'E.	
	Land High & rolling. Soil, second rate.	
	Timber, Fir, Cedar, Pine, Sugar Pine, Laurel, Maple ,	
	& Chinquapin.	
	Underbrush, Maple, Fir, Laurel & Alder.	
From SW. cor. sec. 7. T. 30. S. R. 1 W. offset East 5 miles.,		
thence North one mile, thence East one mile, thence		
North one mile to cor. Tps. 29 & 30 S. Rs., 1 E. & one W.		
	Set post , from which	
	A fir, 15 ins. diam., bears N.31*W., 21 lks. dist.	
	A fir, 10 ins. diam., bears N.45*E., 33 lks. dist.	
	A Laurel, 12 ins. diam., bears S.70*W., 38 lks. dist.	
	A Laurel, 12 ins. diam., bears S.10*E., 26 lks. dist.	
	West on S. Bdy. sec. 36.	
	Va. 18*45'E.	
40.00	Set $\frac{1}{2}$ sec. post, from which	+ 100
	A fir, 12 ins. diam., bears S.87*W., 31 lks. dist.	
	A fir, 12 ins. diam., bears N.80*W., 27 lks. dist.	
65.65.	Branch 5 lks. wide C. NE.	- 50