

County Surveyor's Record, Douglas County, Oregon

Portion of the North Bdy. of T, 30 S., R 1 W.,

CHAINS

November 10.

I return to the cor. of secs. 5, 6, 31 and 32

Thence I run

N.89*53'E. on a true line bet. secs. 5 and 32.

Over mountainous land, heavily timbered and covered with dense undergrowth.

Desc. gradual SE. slope.

- 7.10 Settlers trail, bears NW. and SE.
- 27.25 Ravine course S.
- 40.00 Set an iron stone 24x20x8 ins. 18 ins in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face., from which
 - A fir, 24 ins. diam., bears N.57*W., 16 lks. dist., marked, $\frac{1}{4}$ S 32 B. T.
 - A fir, 14 ins. diam., bears S.34*W., 39 lks. dist., marked, $\frac{1}{4}$ S 5 B. T.
- 40.32 The corner originally set by me under contract No. 757, as the $\frac{1}{4}$ cor. bet. secs. 5 and 32, bears N. 17 lks. dist., I destroy the cor. and marks on bearing trees.
- 57.25 Settlers trail bears NE. and SW.
- 69.75 Creek, 5 lks. wide, course S.
- 77.25 Creek, 5 lks. wide, course S.
- 80.00 Set a basalt stone, 20x12x10 ins., 15 ins. in the ground for cor. of secs. 4, 5, 32 and 33, marked with 4 notches on E. and 2 notches on W. edges., from which
 - A white oak, 8 ins. diam., bears N.38*E., 72 lks. dist., marked T 29 S R 1 W S 33 B. T.
 - A fir, 20 ins. diam., bears S 55*E., 8 lks. dist., marked T 30 S R 1 W S 4 B. T.
 - A fir, 12 ins. diam., bears S.28*W., 27 lks. dist., marked T 30 S R 1 W S 5 B. T.
 - A fir, 10 ins. diam., bears N.81*W., 53 lks. dist., marked T 29 S R 1 W S 32 B. T.