

Subdivisional Lines of T. 29 S. R. 1 W.,  
As Surveyed by, Ernest P. Rands, Deputy Surveyor,  
Under Contract No. 790 dated Oct. 18, 1909.

CHAINS

At the cor. of secs. 35 and 36, on the S. Bdy. of the Tp.  
heretofore described.

Thence I run  
N.0\*1'W. bet. secs. 35 and 36.  
Over rolling ground through heavy timber and dense  
undergrowth.

18.00 Desc. 100 ft.

26.00 Foot of descent, bears E. and W.  
Thence over level bench.

32.00 Desc. 100 ft.

40.00 Foot of descent, bears E. and W.  
A fir, 30 ins. diam., for  $\frac{1}{4}$  sec. cor. I mark  $\frac{1}{4}$  S 36 on E.  
side and 35 on W. side, from which  
A fir, 15 ins. diam., bears S.82\*E., 28 lks. dist.,  
marked  $\frac{1}{4}$  S 36 B T.  
A fir, 24 ins. diam., bears N.43\*W., 44 lks. dist.,  
marked  $\frac{1}{4}$  S 35 B T.  
Thence over level bench.

66.60 A fir, 60 ins. diam., on line I mark with 2 notches on N.  
and S. sides.

76.55 Settlers' trail, bears E. and W.

80.00 Set a basalt stone, 18x10x6 ins. 12 ins. in the ground  
for cor. of secs. 25, 26, 35 and 36, marked with 1  
notch on S. and E. edge, from which  
A fir, 24 ins. diam., bears N.65\*E., 58 lks. dist.,  
marked T 29 S R 1 W S 25 B T.  
A fir, 24 ins. diam., bears S.80\*E., 26 lks. dist.,  
marked T 29 S R 1 W S 36 B T.  
A fir, 24 ins. diam., bears S.71\*W., 42 lks. dist.,  
marked T 29 S R 1 W S 35 B T.  
A fir, 30 ins. diam., bears N.74\*W., 29 lks. dist.,  
marked T 29 S R 1 W S 26 B T.