

Subdivisional Lines of T. 29 S., R. 1 W.,

CHAINS

- Over steep descent through heavy timber and dense undergrowth.
- 19.50 Left bank of the N. Fork of the S. Umpqua River, 150 lks. wide, course W. 1000 ft. below the sec. cor.
- 21.00 Right bank of River.
- 21.75 Ascend.
- 22.25 River trail, bears E. and W.
- 26.00 Rock bluff, 30 ft. high, bears E. and W.
- 31.00 Rock cliff, 20 ft. high, bears E. and W.
- 38.00 Enter level bench, 600 ft. above river, bears NE. and SW.
- 40.00 A point on E. edge of a circular pond of stagnant water 1.00 ch. in diam.
- Set a basalt stone, 18x10x6 ins. 12 ins. in the ground, for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, from which
- A fir, 18 ins. diam., bears S.30*E., 54 lks. dist., marked $\frac{1}{4}$ S 23 B T.
- A fir, 30 ins. diam., bears S.30*W., 85 lks. dist., marked $\frac{1}{4}$ S 22 B T.
- 47.00 Leave bench, bears E. and W.
- Begin steep asc.
- 61.00 Enter brushy opening, bears NE. and SW.
- Thence asc. across steep W. slope.
- 72.00 Top of asc. on steep W. ^{slope} ~~slope~~ about 2000 ft. above the river.
- Thence across steep rocky W. slope.
- 80.00 Set a basalt stone, 18x12x10 ins. 12 ins. in the ground, for cor. of secs. 14, 15, 22 and 23, marked with 3 notches on S. and 2 notches on E. edge, from which
- A fir, 48 ins. diam., bears N.22*E., 44 lks. dist., marked T 29 S R 1 W S 14 B T.
- A laurel, 10 ins. diam., bears S.40*E., 65 lks. dist., marked T 29 S R 1 W S 23 B T.
- A fir, 40 ins. diam., bears S.54*W., 49 lks. dist., marked T 29 S R 1 W S 22 B T.