

75

Re-survey of a Portion of the Willamette Meridian.

CHAINS

From this cor. the $\frac{1}{4}$ sec. cor. on E. Bdy. sec. 1, T 30 S, R 1 W, bears S. 4.06 chs. dist. This cor. is a basalt stone, 5x12x5 ins. above ground, firmly set, and marked and witnessed as described by the Surveyor General.

I re-establish this cor. in its original position as the $\frac{1}{4}$ sec. cor. on E. Bdy. sec. 1, T 30 S R 1 W, only, as follows:

Stone already set and described, from which

A fir, 24 ins. diam., bears S.30*W., 54 lks. dist., marked $\frac{1}{4}$ S 1 B T.

A fir, 40 ins. diam., bears N.66*W., 43 lks. dist., marked $\frac{1}{4}$ S 1 B T.

I obliterate marks on former bearing tree in T 30 S, R 1 E.

Thence I run

North on W. Bdy. sec. 31, retracing Willamette Meridian.

Over mountainous land, heavily timbered and covered with dense undergrowth.

Desc. NE. slope.

9.00 Small swale, course E.

Gradually Asc. SE. slope.

16.00 Low ridge, bears E. and W.

22.00 Enter Willow burn.

36.50 Low ridge, bears E. and W.

36.85 Trail bears, E. and W.

40.00 Set a basalt stone, 15x10x8 ins. 10 ins. in the ground, for $\frac{1}{4}$ sec. cor. on W. Bdy. sec. 31, marked $\frac{1}{4}$ on E. face from which

A fir, 5 ins. diam., bears N.19*E., 4 lks. dist., marked $\frac{1}{4}$ S 31 B T.

A madrone, 6 ins. diam., bears S.42*E., 48 lks. dist., marked $\frac{1}{4}$ S 31 B T.

40.90 Trail to Acker's, bears E. and W.