

## Re-survey of a Portion of the Willamette Meridian.

## CHAINS

42.11 A pine, 40 ins. diam., marked with 2 notches on N. and S. sides.

43.20 The SE. cor. of T. 29 S, R 1 W, which is a basalt stone 4x8x8 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General.

68.00 Divide bet. N. and S. Forks of S. Umpqua river bears E. and W.

Desc. N. slope.

80.00 Set a conglomerate stone, 18x12x6 ins. 12 ins. in the ground, for cor. of secs. 30 and 31, marked with 5 notches on N. and 1 notch on S. edge, from which  
 A hemlock, 9 ins. diam., bears N.44\*E., 10 lks. dist., marked T 29 S R 1 E S 30 B T.  
 A hemlock, 6 ins. diam., bears S.45\*E., 5 lks. dist., marked T 29 S R 1 E S 31 B T.

Land, mountainous.

Soil, loam and stony, 2nd. and 3rd. rate.

Timber, fir, pine, cedar.

Undergrowth, willow, arrow wood, fir and hemlock.

September 26, 1910.

At the cor. of secs. 30 and 31.

Thence I run

North on W. Bdy. sec. 30, retracing the Willamette Meridian.

Over mountainous land, heavily timbered and covered with dense undergrowth.

Desc. NE. slope.

3.20 The  $\frac{1}{4}$  sec. cor. on E. Bdy. sec. 36, T 29 S, R 1 W, which is a basalt stone, 5x14x4 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General.

I re-establish this cor. in its original position as the