

Re-survey of a Portion of the Willamette Meridian.

CHAINS	
	<p>$\frac{1}{4}$ sec. cor. on E. bdy. sec. 36, T.29 S, R 1 W, only as follows:</p> <p>Stone already set and described, from which</p> <p>A fir, 16 ins. diam., bears S.79*W., 44 lks. dist., marked $\frac{1}{4}$ S 36 B T.</p> <p>A fir, 10 ins. diam., bears N.40*W., 80 lks. dist., marked $\frac{1}{4}$ S 36 B T.</p> <p>I obliterate marks on former bearing tree in T 29 S, R 1 E.</p>
19.85	Ravine, course NE.
25.25	Ravine, course E.
30.10	Creek, 1 lk. wide, course NE.
40.00	<p>Set a basalt stone, 18x10x4 ins. 12 ins. in the ground for $\frac{1}{4}$ sec. cor. on W. bdy. sec. 30, marked $\frac{1}{4}$ on E. face, from which</p> <p>A fir, 8 ins. diam., bears N.18*E., 106 lks. dist., marked $\frac{1}{4}$ S 30 B T.</p> <p>A fir, 7 ins. diam., bears S.15*E., 12 lks. dist., marked $\frac{1}{4}$ S 30 B T.</p>
43.39	The cor. of secs. 25 and 36, T 29 S, R 1 W, which is a basalt stone, 5x12x10 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General.
80.00	<p>Set a conglomerate stone, 15x8x8 ins. 10 ins. in the ground, for cor. of secs. 19 and 30, marked with 4 notches on N. and 2 notches on S. edge, from which</p> <p>A fir, 9 ins. diam., bears N.83*E., 66 lks. dist., marked T 29 S R 1 E S 19 B T.</p> <p>A fir, 16 ins. diam., bears S.64*E., 20 lks. dist., marked T 29 S R 1 E S 30 B T.</p> <p>From this cor. ^{the} of $\frac{1}{4}$ sec. cor. on E. bdy. ^{of} sec. 25, T 29 S, R 1 W, which is a basalt stone, 5x8x6 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General, bears N. 3.47 chs. dist.</p> <p>I re-establish this cor. in its original position as the $\frac{1}{4}$ sec. cor. on E. bdy. sec. 25, T 29 S, R 1 W, only as</p>