

Re-survey of a Portion of the Willamette Meridian.

CHAINS

follows:

Stone already set and described, from which

A fir, 36 ins. diam., bears S.60*W., 38 lks. dist.,
marked $\frac{1}{4}$ S 25 B T.

A madrone, 20 ins. diam., bears N.56*W., 6 lks. dist.,
marked $\frac{1}{4}$ S 25 B T.

I destroy marks on former bearing tree in T 29 S, R 1 E,
Land, mountainous.

Soil, loam and stony, 2nd and 3rd rate.

Timber, fir, cedar and hemlock.

Undergrowth, fir, hemlock, arrowwood and vine maple.

September 27, 1910.

Retracement and Resurvey of Willamette Meridian,
Through a Portion of Township 29 South.
Executed by, Fred Mensch, U.S. Cadastral Engineer,
Under Special Instructions, dated Dec. 21, 1920.

I commence at the cor. of secs. 19 and 30, on W. bdy. of
T. 29 S., R. 1 E.

Thence N., retracing E. bdy. of sec. 25, T. 29 S., R. 1 W.

3.44 Intersect $\frac{1}{4}$ sec. cor. on E. bdy. of sec. 25.

43.57 Intersect the cor. of secs. 24 and 25, T. 29 S., R. 1 W.

The bearing and length of this line, from cor. of secs.

19 and 30, to $\frac{1}{4}$ sec. cor. of sec. 25, is N. 3.44 chs.,from $\frac{1}{4}$ sec. cor. to cor. of secs. 24 and 25, N. 40.13 chs.

Thence N. retracing E. bdy. of sec. 24, T. 29 S., R. 1 W.

39.83 The $\frac{1}{4}$ sec. cor. bears E., 14 lks. dist.,

79.87 Fall 26 lks. W. of cor. of secs. 13 and 24, T. 29 S., R 1 W.

The bearing and length of the S. half of this line is,

N.0*12'E., 39.83 chs., and of the N. half,

N.0*10'E., 40.04 chs.

Thence N. retracing E. bdy. of sec. 13, T. 29 S., R. 1 W.