

Retracement and Resurvey of Willamette Meridian.

CHAINS

39.99 The $\frac{1}{4}$ sec. cor. bears E., 10 lks. dist.

80.04 Fall 24 lks. W. of cor. of secs. 12 and 13, T. 29 S.,
R. 1 W.

The bearing and length of the S. half of this line is,
N.0°09'E., 39.99 chs. and of the N. half,
N.0°12'E., 40.05 chs.

Thence N. retracing E. Bdy. of sec. 12, T. 29 S.,
R. 1 W.

39.98 The $\frac{1}{4}$ sec. cor. bears E., 16 lks. dist.

80.01 Fall 30 lks. W. of the cor. of secs. 1 and 12, T. 29 S.,
R. 1 W.

The bearing and length of the S. half of this line is,
N.0°14'E., 39.98 chs., and of the N. half,
N.0°12'E., 40.03 chs.

Thence N. retracing E. Bdy. of sec. 1, T. 29 S., R. 1 W.

39.98 Fall 19 lks. W. of the $\frac{1}{4}$ sec. cor.

The bearing and length of this line, to the $\frac{1}{4}$ sec. cor.,
is N.0°16'E., 39.98 chs.

From the cor. of secs. 19 and 30, on W. Bdy. of T. 29 S.,
R. 1 E., which is a conglomerate stone, 5x8x8 ins.
above ground, firmly set, marked and witnessed as
described by the Surveyor General.

North, resurveying W. Bdy. of sec. 19.

Over mountainous land, through heavy timber and dense
undergrowth.

Along ridge, bears N. and S.

3.44 Intersect the $\frac{1}{4}$ sec. cor. on E. Bdy. of sec. 25, T. 29 S.,
R. 1 W., which is a basalt stone, 5x8x6 ins. above
ground, firmly set, marked and witnessed as described
by the Surveyor General.

Desc. 325 ft. on NE. slope.