

Retracement and Resurvey of Willamette Meridian.

CHAINS	
24.00	Draw, course E., asc. 20 ft. on SE. slope.
26.25	Rocky point, slopes E., desc. 100 ft. over bluff.
26.80	Foot of bluff, desc. 350 ft. on NE. slope, to
40.10	Midpoint on W. Bdy. of sec. 19.
	Set a basalt stone, 20x12x8 ins. 12 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 19 only, marked $\frac{1}{4}$ on E. face, from which
	A fir, 7 ins. diam., bears N.48*E., 21 lks. dist., marked $\frac{1}{4}$ S. 19 B T.
	A fir, 20 ins. diam., bears S.22*E., 15 lks. dist., marked $\frac{1}{4}$ S 19 B T.
	No iron post available for this corner.
	Desc. 45 ft. on N. slope, to
43.57	Intersect the cor. of secs. 24 and 25, T. 29 S., R. 1 W., which is a basalt stone, 4x12x6 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General.
	Thence N.0*12'E.
	Desc. 425 ft. on broken NE. slope, to spur.
3.30	Creek, 2 lks. wide, course NE.
16.20	Ravine, course NE.
30.75	Spur, slopes NE., desc. 275 ft. on NW. slope, to
36.63	Point of intersection with line bet. secs. 18 and 19, determined as hereinafter set forth.
	Set a basalt stone, 20x10x10 ins. 15 ins. in the ground, for closing cor. of secs. 18 and 19, marked CC on E., with 3 grooves on N. and S. faces, from which
	A cedar, 20 ins. diam., bears N.33*E., 19 lks. dist., marked T 29 S R 1 E S 18 C C B T.
	A hemlock, 6 ins. diam., bears S.50*E., 8 lks. dist., marked T 29 S R 1 E S 19 C C B T.