

Retracement and Resurvey of Willamette Meridian.

CHAINS

A fir, .20 ins. diam., bears N.15*E., 94 lks. dist.,
marked $\frac{1}{4}$ S 18 B T.

A fir, 36 ins. diam., bears S.34*E., 120 lks. dist.,
marked $\frac{1}{4}$ S 18 B T.

No iron post available for this corner.

Thence over W. slope.

40.04 Intersect the cor. of secs. 13 and 24, T 29 S., R. 1 W.,
which is a basalt stone, 5x12x8 ins. above ground,
firmly set, marked and witnessed as described by the
Surveyor General.

Thence N.0*09'E.

Asc. 75 ft. on SW. slope.

6.20 Spur, slopes SW., desc. 125 ft. on NW. slope.

11.30 Draw, course SW., asc. 135 ft. on SE. slope.

24.00 Spur, slopes SW., desc. 80 ft. on NW. slope.

29.30 Creek, 1 lk. wide, course SW., asc. 140 ft. on SE. slope, to

36.54 Point of intersection with line bet. secs. 7 and 18,
determined as hereinafter set forth.

Set a basalt stone, 20x8x6 ins. 15 ins. in the ground,
for closing cor. of secs. 7 and 18, marked CC on E.,
with 2 grooves on N., and 4 grooves on S. face, from which

A fir, 14 ins. diam., bears N.59*E., 64 lks. dist.,
marked T 29 S R 1 E S 7 C C B T.

A fir, 10 ins. diam., bears S.41*E., 41 lks. dist.,
marked T 29 S R 1 E S 18 C C B T.

No iron post available for this corner.

Land, mountainous.

Soil, clay loam, 2nd. and 3rd. rate.

Timber, fir, cedar, pine and hemlock.

Undergrowth, snow brush, chinquapin, hazel and vine maple.